



EVO-STIK INSTANT GRAB WALL TILE ADHESIVE

READY-MIXED CERAMIC WALL TILE ADHESIVE

TECHNICAL SHEET NO: TDS00445 21/08/2026

SMART ADVANTAGES

- Showerproof
- Thin-bed adhesive
- High-grab, non-slip formula

DESCRIPTION

EVO-STIK Instant Grab Wall Tile Adhesive is a ready-to-use, instant grab adhesive for use on dry, internal walls and areas subject to some splashing and condensation such as shower walls, kitchens and bathrooms.

The adhesive is suitable for fixing tiles to most common substrates, including plaster, plasterboard, existing glazed tiles, cement renders and tile backer boards (drying times may vary), provided surfaces are sound, rigid, dry and clean.

This product is intended for internal wall applications only. For floor tiling, external use, or areas subject to continuous water immersion, the use of an EVO-STIK cement-based tile adhesive is recommended.



TECHNICAL CHARACTERISTICS

Colour	Buff
Form	Structured paste
Composition	Acrylic aqueous emulsion with inorganic extenders
Application temperature	+5°C to +35°C
Drying time	Set time: 24 hours on standard backgrounds 72 hours on impervious backgrounds (at +20°C, depending on application thickness, ambient temperature and humidity)
UKCA / CE classification	D1TE

COVERAGE

- Approx. 1.1m² per economy tub
 - Approx. 2.7m² per standard tub
 - Approx. 5.5m² per large tub
 - Approx. 11m² per extra large tub
- (depending on the smoothness and absorbency of the substrate, the adhesive bed thickness, the type of tile and trowel used)

APPLICATION

IMPORTANT: Before using EVO-STIK Instant Grab Wall Tile Adhesive, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Ensure all substrates are clean, dry, sound, flat, free from cracks, structural defects and contaminants that may impair adhesion, including dust, oil, grease, paint, varnish, wax polishes, sealers, loose materials or other surface contamination.
- Substrates must be sufficiently strong and rigid to support the combined weight of the tiles and adhesive.
- Remove all wallpaper and lightly abrade painted surfaces using a coarse sandpaper to provide a key.
- Fill any holes or cracks using a suitable wall filler and allow to dry fully.
- When tiling over existing ceramic tiles, thoroughly clean the surface and prime with a suitable Bostik Primer. Any loose or hollow-sounding tiles should be re-fixed prior to application.
- Where tiling onto dusty plaster, prime as detailed below and allow to dry fully before application.
- New plaster must be allowed to dry fully for at least 4 weeks, and cement renderings for at least 2 weeks, prior to tiling.
- The wall must be structurally sound and capable of supporting the combined weight of the tiles and adhesive. The maximum recommended load for plaster is 20kg per m².
- The temperature of the application environment must be stable and maintained between +5°C and +35°C throughout the application and drying of the tile adhesive.
- Where the substrate is to be tanked using products such as Bostik FLEXIBLE TANKING SYSTEM or Bostik ANTI-FRACTURE MEMBRANE, a cement-based tile adhesive may be more suitable. Contact Bostik Technical Services for further advice.
- Plan the tile layout to avoid narrow cuts above or below the batten. Where possible, position cut tiles at corners or edges where they are less visible.

PRIMING

- Priming is recommended on certain substrates as it will aid adhesion.

Wall substrate	Primer
Porous/dusty surfaces	EVO-STIK Flexible Primer (diluted 1 : 2 with water)
Plaster	Contact Bostik Technical Services
Existing ceramic tiles	Contact Bostik Technical Services

APPLICATION

Fixing

- Stir the adhesive thoroughly before use.
- Apply the adhesive to the wall using a notched trowel, spreading evenly to a depth of 3mm.
- Spread only sufficient adhesive for approximately 20 minutes of tiling (approx. 1m²).
- In areas subject to frequent wetting, tiles must be fixed onto a solid bed of adhesive.

- Press the tiles into the adhesive using a slight twisting action. Periodically lift a tile to check that the adhesive has fully covered the back of the tile.
- The use of tile spacers is recommended to ensure consistent joint widths. Grout joints should be between 1.5mm and 3mm.
- Continue tiling in small sections, finishing with the bottom row. Ideally, position cut tiles at edges.
- Remove excess adhesive from the tile surface immediately using a tiling sponge or damp cloth.

Grouting

- Allow a minimum of 24 hours for the adhesive to dry before grouting. On non-porous surfaces, allow 48 to 72 hours under good drying conditions. Lower temperatures will extend drying times.
- Follow the tile manufacturer's recommendations regarding protection and sealing of tiles before and after grouting.
- For best results, use an EVO-STIK tile grout.

CLEANING

- Clean tools and equipment with warm, soapy water immediately after use. Remove surplus adhesive from surfaces with a damp cloth whilst it is still wet. Dried and hardened adhesive can only be removed mechanically.

STORAGE

- Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 24 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

PRECAUTIONS IN USE

For any substrates not mentioned in this technical data sheet, please contact Bostik Technical Services.

Do not tile onto substrates in excessively hot conditions, or when the temperature is below +5°C. Drying times will be extended if the product is applied on to non-absorbent surfaces, or not in accordance with the instructions. It is not suitable for use on floors or in areas subject to continuous water immersion, such as swimming pools.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for EVO-STIK Instant Grab Wall Tile Adhesive, available at www.bostik.com/uk.

PACKAGING

Product codes	30811581	Economy tub x 12
	30812627	Standard tub

	30812628	Large bucket
	30812629	Extra large bucket

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone:	01785 272625
Sales:	customer.service@bostik.com
Technical advice:	technical.service@bostik.com
Safety data sheets:	sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.