



EVO-STIK Plumber's Mait

NON-SETTING SANITARY PUTTY

Date: 12 July 2018

FactSheet No.: TDS00331

YOUR SMART ADVANTAGES

- Waterproof, non-setting putty ideal for sanitary joints.
- Permanently flexible allows joint movement
- Adheres to metal, PVC, vitreous enamels and ceramics

USES

A non-setting hand-applied putty for sanitary joints. For use in the installation of drainpipes, sinks and valves. Plumber's Mait seals areas exposed to unpressurised water, preventing leaks and seepage. It can also be used to seat fixtures such as sinks, toilets and vanity units in conjunction with mechanical fixings.

It can be used at the base of taps and other sink features before setting them onto the sink.

Plumber's Mait can be used on drains in kitchen and bathroom sinks, in bath drains and to seal toilets to bathroom floors.

PRODUCT CHARACTERISTICS

Colour	Light beige	
Form	Non-setting putty	
Specific Gravity	2.0 g/cm ³	
Composition	N/A	
Product Code	30812666	750g x 12
	30812668	1.5kg x 12
	30812669	3kg x 1
Storage/Shelf Life	Store for up to 24 months from date of manufacture when stored in original, unopened packaging under cool, dry conditions within the	

temperature range of +5°C to +23°C and out of direct sunlight. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +30°C
Service Temperature	N/A
Coverage	Varies depending on application
Drying Times	Remains permanently flexible
Tensile Strength	N/A
Modulus at 100% Elongation	N/A
Elongation at Break	N/A
Slump Resistance	N/A
Movement Accommodation	±5%

DIRECTIONS FOR USE

IMPORTANT: Before using EVO-STIK Plumber's Mait refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

All surfaces should be clean, dry and free from grease and loose materials. This is best achieved by wiping with a clean cloth followed by a final wipe over with a small piece of Plumber's Mait.

APPLICATION

To seal spigot and socket joints, e.g. WC pan to soil pipe:

Pack untarred hemp evenly around the spigot to ensure a concentrated fit. Plumber's Mait should then be packed into the gap using a putty knife and smoothed off.

As a bedding mastic:

Apply an even bead of Plumber's Mait to the seating before fitting and securing the other component.

Plumber's Mait is a non-setting putty so it remains permanently flexible. It can, however, be overpainted.

CLEANING

Remove excess Plumber's Mait from surfaces by rubbing off with another piece of Plumber's Mait. Clean hands after use with soap and water.

PRECAUTIONS IN USE

If medical advice is needed, have container or label at hand. Keep out of reach of children. Avoid contact with skin and eyes.

Plumber's Mait can stain some porous materials such as granite, marble and synthetic marble. Avoid using it on areas that stain easily.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for EVO-STIK Plumber's Mait, available at www.bostik.co.uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com