



# EVO-STIK Sticks Like Sealant White

A High-quality hybrid sealant

TECHNICAL SHEET NO: TDS02068 02/07/2024

## SMART ADVANTAGES

- Sticks to wet Surfaces
- Ultra-flexible no compromise sealant
- Paintable when dry

## DESCRIPTION

EVO-STIK Sticks Like Sealant White is specially formulated using advanced hybrid SMP technology. EVO-STIK Sticks Like Sealant White provides a strong, flexible bond for most building materials and can even be used on wet surfaces. EVO-STIK Sticks Like Sealant White cures under the influence of humidity to form a durable elastic rubber, which is almost odourless.

EVO-STIK Sticks Like Sealant White is ideal for most sealing jobs, indoors and outdoors.

It is suitable for sealing around window and door frames, in bathrooms and kitchens, and can also be used for sealing roof and guttering, even when it's raining.

Meeting the requirements of BS EN 15651-1, 3, 4:2012 for façade elements, sanitary joints, and pedestrian walkways.



## TECHNICAL CHARACTERISTICS

|                         |                                    |
|-------------------------|------------------------------------|
| Colour                  | White                              |
| Form                    | Soft gunnable paste                |
| Specific Gravity        | 1.58 g/ml                          |
| Shore A hardness        | 54                                 |
| Composition             | Moisture curing SM Polymer system. |
| Application Rate        | 100 - 300 g/min                    |
| Application temperature | +5°C to +40°C                      |
| Curing time*            | Approx.10 minutes                  |
| Elongation at Break     | 325%                               |
| Joint Movement          | ± 25%                              |
| Temperature Resistance  | -40°C to +90°C                     |
| Tensile Strength        | 2.05 N/mm <sup>2</sup>             |
| 100% Modulus            | 1.2N/mm <sup>2</sup>               |
| Flow                    | <2mm                               |

\* Cure through: Approx. 2mm/24 hours at 23°C/ 50% RH. Fully cured in approx. 24 hours depending on bead width, temperature, and humidity.

Page 1 of 3

## COVERAGE

- Approximately 11 metres using a 5mm bead.

## APPLICATION

**IMPORTANT:** Before using EVO-STIK Sticks Like Sealant White refer to the relevant Health & Safety Data Sheet, available at [www.bostik.com/uk](http://www.bostik.com/uk).

### PREPARATION

- Surfaces must be sound, clean, and free from any contaminants such as dust, oil, grease, and any loose material.
- Cut off the dome at the top of the cartridge taking care not to damage the thread. Cut the nozzle to the desired width and angle. Screw the nozzle onto the cartridge.
- Insert the cartridge into a professional cartridge gun and repeatedly squeeze the trigger until the sealant appears.

### SEALANT APPLICATION

- Place the nozzle at the start of the gap, and gently squeeze the trigger. Push forward slowly, ensuring that contact is made by the sealant with both sides of the gap. At the end of the run, release the trigger and press the plunger release plate of the gun.
- Product must be gunned firmly into the joints to ensure good adhesion to the joint surfaces.
- Smooth the sealant with a wet, round ended tool (do not use a wetted finger), remove any excess with a cloth moistened with white spirit.
- After use, ensure to wipe away any excess sealant from the nozzle.

## CLEANING

- Uncured product may be removed using cloths lightly dampened with white spirit, after carefully scraping off the bulk.
- Cured product requires mechanical removal.

## STORAGE

- Store for up to 18 months from the date of manufacture when stored in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +25°C and out of direct sunlight. Protect from frost.

## PRECAUTIONS IN USE

EVO-STIK Sticks Like Sealant White is not suitable for PE, PP, PC, PMMA, PTFE, Soft plastics, neoprene, and bituminous substrates. EVO-STIK Sticks Like Sealant White should not be used in swimming pools. Do not use for aquarium applications. Do not submerge under water. EVO-STIK Sticks Like Sealant White is not suitable for natural stone.

EVO-STIK Sticks Like Sealant White is paintable after 24 hours with most paints (avoid alkyd resin-based paints). It is recommended to test compatibility with any paints prior to applications.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit [www.bostik.com/uk](http://www.bostik.com/uk) for advice to determine suitability for use.

Recommendations and suggestions are for guidance only since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for EVO-STIK STICKS LIKE SEALANT WHITE, available at [www.bostik.com/uk](http://www.bostik.com/uk).

## PACKAGING

|               |          |          |
|---------------|----------|----------|
| Product codes | 30613624 | C20 X 12 |
|---------------|----------|----------|

|  |
|--|
| 1213 <b>UK<br/>CA</b> 22   |
| DOP available on:<br><a href="http://www.bostik.com/uk">www.bostik.com/uk</a><br>TDS Number: TDS02068<br>DoP nr:<br>White: 656-22-3088 |
| <b>EN 15651-1</b><br>F-EXT-INT-CC<br><br><b>EN 15651-3</b><br>S<br><br><b>EN 15651-4</b><br>PW-EXT-INT-CC                              |
| Façade, Sanitary &<br>Pedestrian Walkways<br>Sealant   |

|  |
|--|
| 1213 <b>CE</b> 22  |
| DOP available on:<br><a href="http://www.bostik.com/uk">www.bostik.com/uk</a><br>TDS Number: TDS02068<br>DoP nr:<br>White: 656-22-3088 |
| <b>EN 15651-1</b><br>F-EXT-INT-CC<br><br><b>EN 15651-3</b><br>S<br><br><b>EN 15651-4</b><br>PW-EXT-INT-CC                              |
| Façade, Sanitary &<br>Pedestrian Walkways<br>Sealant   |

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left hand corner on the front of this document.

|                    |                    |  |
|--------------------|--------------------|--|
| Sales              | Tel: 0844 371 1192 | <a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>   |
| Technical Advice   | Tel: 0844 371 1197 | <a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a> |
| Safety Data Sheets | Tel: 01785 272625  | <a href="mailto:sds.box-eu@bostik.com">sds.box-eu@bostik.com</a>               |

Bostik Ltd  
Common Road,  
Stafford, ST16 3EH, UK  
Phone: +44 (0)1785 272625  
[www.bostik.com/uk](http://www.bostik.com/uk)

**BOSTIK HOTLINE**

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.