



# EVO-STIK Standard Set Floor & Wall Tile Adhesive

## FOR FIXING CERAMIC TILES

TECHNICAL SHEET NO: TDS00328 19/12/2024

### SMART ADVANTAGES

- Extended setting time
- Excellent adhesion
- Weather resistant

### DESCRIPTION

EVO-STIK Standard Set Floor & Wall Tile Adhesive is a grey cement based adhesive that will set in 24 hours. It has been designed to allow more working time, making it ideal for use in awkward areas to tile. It is suitable for use with, ceramic and dark natural stone tiles. Waterproof and frost resistant, it is suitable for interior and exterior use.

EVO-STIK Standard Set Floor & Wall Tile Adhesive can be applied directly onto most common substrates including sand/cement screeds, plasterboard, tile backerboard and sealed plaster.



### TECHNICAL CHARACTERISTICS

<b>Colour</b>	Grey
<b>Form</b>	Powder
<b>Composition</b>	Blend of cement, polymers and selected fillers
<b>Application temperature</b>	+5°C to +35°C
<b>Gauging liquid</b>	Water
<b>Application thickness</b>	3mm to 6mm
<b>Pot life</b>	Approx. 3-4 hours at 20°C (depending on ambient temperature and humidity) Set time: 24 hours
<b>Drying times</b>	Grouted: after 24 hours Foot traffic: 24 hours (at +20°C, depending on application thickness, ambient temperature and humidity)
<b>UKCA/ CE classification</b>	C1T

### COVERAGE

- Approx. up to 7m<sup>2</sup> per bag (depending on the smoothness and absorbency of the floor surface)

## APPLICATION

**IMPORTANT:** Before using EVO-STIK Standard Set Floor & Wall Tile Adhesive, refer to the relevant Health & Safety Data Sheet, available at [www.bostik.com/uk](http://www.bostik.com/uk).

### PREPARATION

- Ensure substrates are clean, dry, sound, flat, strong and rigid enough to support tiles, free from cracks, structural defects and contaminants that may prevent adhesion (e.g., dust, oil, grease, paint, varnish, wax polishes, sealers, loose materials and other surface contaminants).
- The temperature of the application environment must be stable and maintained between +5°C and +35°C throughout the application and drying of the tile adhesive.
- If using over existing ceramic tiles, it is necessary to clean and prime with a suitable Bostik Primer. Re-fix tiles where loose.
- Remove any loose surface coverings.

### FLOOR TILING PREPARATION

- New cementitious screeds must be sufficiently dry. It is recommended a minimum 3 weeks old and new concrete a minimum of 6 weeks before receiving tiling products.
- If tiling onto calcium sulphate screeds, contact Bostik Technical Services.

### WALL TILING PREPARATION

- Fill any holes or cracks in the walls.
- If tiling onto plaster, prime with a suitable Bostik primer and allow to dry for one hour. The plaster must be strong enough to take the complete weight of the subsequent tiling and adhesive. The maximum weight the plaster can take is 20kg per 1m<sup>2</sup>.
- If tiling onto plasterboard, ensure the substrate has been primed with a suitable Bostik primer. The maximum weight the plasterboard can take is 32kg per 1m<sup>2</sup>.

### PRIMING

- Priming is recommended on certain substrates as it will aid adhesion.

Wall Substrate	Priming
Porous/dusty surfaces	EVO-STIK Flexible Primer (diluted 1 : 2 with water)
Plaster	Contact Bostik Technical Services
Existing ceramic tiles	Contact Bostik Technical Services
Floor Substrate	
Porous/dusty surfaces*	EVO-STIK Flexible Primer (diluted 1 : 2 with water)
Calcium sulphate- based screed	Contact Bostik Technical Services

\*The surface needs to be vacuumed to ensure loose particles are removed.

### MIXING

- Pour 5-5.4L of clean cold water into a clean mixing bucket. Gradually add the 20kg bag of EVO-STIK Standard Set Floor & Wall Tile Adhesive until a thick creamy consistency is achieved.

- The mixture is ready for use immediately. No water should be added after the original mixing.

### FIXING

- Spread the adhesive evenly using a notched trowel at a depth of 3mm. On uneven surfaces the adhesive may be used to a maximum depth of 6mm.
- Spread the adhesive no greater than 1m<sup>2</sup> or 20 minutes working time.
- Back buttering is recommended for larger tiles.
- **Floor Tiling Fixing:** Use a spirit level across several tiles to ensure that they are laid as evenly as possible.
- A solid bed of adhesive must be used when fixing tiles.
- **Wall Tiling Fixing:** Use a suitable notched trowel.
- Fix tiles using a slight twisting action. Occasionally lift a tile to ensure the adhesive has completely covered the reverse of the tile.

### GROUTING

- Allow 24 hours after application before grouting. For best results use EVO-STIK tile grout.
- Follow the tile manufacturer's instructions for protecting and sealing the tiles before and after grouting.

### CLEANING

- Clean tools and equipment with warm, soapy water immediately after use. Remove surplus adhesive from surfaces whilst it is still wet. Dried and hardened adhesive can only be removed mechanically.

### STORAGE

- Store and transport securely. Store for up to 12 months from date of manufacture in original, unopened packaging, clear of the ground, in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from excessive draughts, frost, damp, condensation and dew.

### PRECAUTIONS IN USE

EVO-STIK Standard Set Floor & Wall Tile Adhesive – for any substrates not mentioned in this Technical Datasheet, contact Bostik Technical Services.

Do not tile onto substrates in excessively hot conditions, or when the temperature is less than +5°C. The mix ratios and temperatures are provided as guidance.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit [www.bostik.com/uk](http://www.bostik.com/uk) for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for EVO-STIK Standard Set Floor & Wall Tile Adhesive, available at [www.bostik.com/uk](http://www.bostik.com/uk).

### PACKAGING

Product code	30812719	20kg bag
--------------	----------	----------

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone: 01785 272625  
Sales: [customer.service@bostik.com](mailto:customer.service@bostik.com)  
Technical advice: [technical.service@bostik.com](mailto:technical.service@bostik.com)  
Safety data sheets: [sds.box-eu@bostik.com](mailto:sds.box-eu@bostik.com)

#### DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

**Bostik Ltd**  
Common Road,  
Stafford, ST16 3EH, UK  
Phone: +44 (0)1785 272625  
[www.bostik.com/uk](http://www.bostik.com/uk)

**BOSTIK HOTLINE**

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.