



EVO-STIK WATERPROOF WALL TILE ADHESIVE

A READY MIXED, WATERPROOF TILE ADHESIVE

TECHNICAL SHEET NO: TDS00376 20/01/2026

SMART ADVANTAGES

- Quick and easy to apply
- Long open time
- A waterproof, non-slip adhesive

DESCRIPTION

EVO-STIK WATERPROOF WALL TILE ADHESIVE is specifically designed for adhering ceramic wall tiles to most sound, interior surfaces. It can be applied onto, plaster, tile backerboard, plasterboard, old, glazed tiles, bricks and cement renders, providing they are rigid and clean.

The product is ideally suited to areas that are subject to infrequent wetting and condensation, such as shower walls, kitchens and bathrooms.

For tiling onto floors, external tiling or areas where the tiles are continuously immersed in water, it is recommended that a EVO-STIK cement-based adhesive is used.



TECHNICAL CHARACTERISTICS

| | |
|--------------------------------|---|
| Colour | Off white |
| Form | Structured paste |
| Composition | An acrylic aqueous emulsion with inorganic extenders |
| Application temperature | +5°C to +35°C |
| Drying times | Set time: 24 hours on standard backgrounds 72 hours on impervious backgrounds (+20°C, depending on application thickness, ambient temperature and humidity) |
| UKCA/ CE classification | D2TE |

COVERAGE

- Approx. 1.1 m² to 11m² dependent on unit size (depending on the smoothness and absorbency of the surface)

APPLICATION

IMPORTANT: EVO-STIK WATERPROOF WALL TILE ADHESIVE, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Ensure substrates are clean, dry, sound, flat, strong and rigid enough to support tiles, free from cracks, structural defects and contaminants that may prevent adhesion (e.g., dust, oil, grease, paint, varnish, wax polishes, sealers, loose materials and other surface contaminants).
- The temperature of the application environment must be stable and maintained between +5°C and +35°C throughout the application and drying of the tile adhesive.
- If using over existing ceramic tiles, it is advisable to clean and prime with a suitable Bostik Primer. Re-fix tiles where loose.
- Remove any loose surface coverings.

WALL TILING PREPARATION

- Fill any holes or cracks in the walls.
- If tiling onto dusty plaster, prime with a suitable Bostik primer and allow to fully dry.
- The wall must be strong enough to take the complete weight of the subsequent tiling and adhesive. The maximum weight the plaster can take is 20kg per 1m².
- New cement rendering should not be tiled over for at least 2 weeks, to allow for shrinkage.
- If the background is to be tanked with products such as Bostik FLEXIBLE TANKING SYSTEM or Bostik ANTI-FRACTURE MEMBRANE, a cementitious adhesive may be more suitable. Contact Bostik Technical Services.

PRIMING

- Priming is recommended on certain substrates as it will aid adhesion.

| Wall Substrate | Priming |
|------------------------|---|
| Porous/dusty surfaces | EVO-STIK FLEXIBLE PRIMER (diluted 1 : 2 with water) |
| Plaster | Contact Bostik Technical Services |
| Existing ceramic tiles | Contact Bostik Technical Services |

FIXING

- Stir the contents before use.
- Spread the adhesive evenly using a notched trowel at a depth of 3mm.
- A solid bed of adhesive must be used when fixing tiles in wet areas.
- Fix tiles using a slight twisting action. Occasionally lift a tile to ensure the adhesive has completely covered the reverse of the tile.
- Spread only sufficient material for about 20 minutes tiling work, approx. 1m²

GROUTING

- Allow at least 24 hours after application before grouting. For best results use a Bostik grout
- Follow the tile manufacturer's instructions for protecting and sealing the tiles before and after grouting.

CLEANING

- Clean tools and equipment with warm, soapy water immediately after use. Remove surplus adhesive from surfaces whilst it is still wet. Dried and hardened adhesive can only be removed mechanically.

STORAGE

- Store and transport securely. Store for up to 24 months from date of manufacture in original, unopened packaging, clear of the ground, in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from excessive draughts, frost, damp, condensation, and dew.

PRECAUTIONS IN USE

EVO-STIK WATERPROOF WALL TILE ADHESIVE – for any substrates not mentioned in this Technical Datasheet, contact Bostik Technical Services.

Do not tile onto substrates in excessively hot conditions, or when the temperature is less than +5°C. Drying time will be extended if the product is applied on to non-absorbent surfaces or not in accordance with the instructions.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for EVO-STIK WATERPROOF WALL TILE ADHESIVE, available at www.bostik.com/uk.

PACKAGING

| | | |
|----------------------|--|---|
| Product codes | 30811582 30812631 30812632 30812633 | Economy x12 Standard Large Extra Large |
|----------------------|--|---|

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone: 01785 272625

Sales: customer.service@bostik.com

Technical advice: technical.service@bostik.com

Safety data sheets: sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.