



EVO-STIK Carpet Adhesive

A SOLVENT BORNE, SPRAYABLE ADHESIVE IN AN AEROSOL CAN

Date: 28 February 2017

Fact Sheet No.: TDS00405

YOUR SMART ADVANTAGES

- Rapid Drying
- Adjustable nozzle
- Strong and flexible

USES

EVO-STIK Carpet Adhesive is a rapid drying, solvent borne aerosol adhesive that is easily applied direct from the can using the adjustable spray nozzle. EVO-STIK Carpet Adhesive provides a strong, flexible bond for many applications where a conventional adhesive would be too difficult to apply. Perfect for spot fixing carpet tiles. It is ideal for bonding all types of flexible foams, fabrics, felts and cork to wood, metal, hardboard, glass, rigid plastics and many other materials.

EVO-STIK Carpet Adhesive can be used to bond thin polythene sheet to other floor surfaces with a reasonable bond.

PRODUCT CHARACTERISTICS

Colour	Light amber, will darken if exposed to light
Form	Liquid spray
Specific Gravity	1.2
Composition	Rapid drying, solvent borne aerosol adhesive
Product Code	30812304 500ml aerosol x 6
Storage/Shelf Life	Store for up to 12 months from date of manufacture when stored in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +25°C and out of direct sunlight.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	5°C-25°C
Coverage	500ml aerosol covers approx. 3.5m ² in a single coat
Drying Times	The adhesive remains "wet" for 15 to 25 minutes. Check that floor coverings are bedded down securely after 2 hours.

DIRECTIONS FOR USE

IMPORTANT: Before using EVO-STIK Carpet Adhesive refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Surfaces to be bonded must be clean, dry and free from grease, dust, polish and loose material.
2. Shake the can well before use.
3. EVO-STIK Carpet Adhesive should be applied directly from the can onto the surfaces to be bonded.
4. Take care to avoid over-spray onto sensitive surfaces.
5. For delicate fabrics, test on a small area before use.

APPLICATION

6. Use the adjustable nozzle to select the required spray pattern.
7. Hold the can 12 - 18cm away from surfaces to be sprayed and ensure that an even coat is applied to both surfaces.
8. Allow the adhesive to become tacky (1 to 3 minutes) and then press the two surfaces together firmly. Some very porous surfaces may require two coats and drying times may be longer.



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

9. For less demanding bonds a single coat may be applied to one surface and when dry the other material can be bonded to it.
10. After use, invert the can and facing away, expel a small amount of propellant to clear the nozzle.
11. Check that the floor covering is bedded down securely after 2 hours.

PRECAUTIONS IN USE

Do not use on plasticised (soft textile) PVC or vinyl tiles, due to plasticiser migration. Not suitable for use with polystyrene and solvent sensitive surfaces. Do not use on or near asphalt or bituminous materials.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for EVO-STIK Carpet Adhesive, available at www.bostik.co.uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.